

DESCRIPTION

BioLube SB RDP is a readily biodegradable, heavy duty rock drill lubricant designed to meet the requirements of pneumatic tools, down-hole and surface drilling equipment. It is formulated with high viscosity index, natural ester base oils, synthetic esters, anti-wear additives, and corrosion protection. The high viscosity index provides superior lubrication in a working hammer. The natural polarity and tackiness of BioLube SB RDP allows the lubricant to adhere to tooling surfaces, further reducing corrosion and wear in the presence of compressed air. This product is ideally formulated for underground mining.

FEATURES & BENEFITS

- High viscosity index to help maintain resistance to flow at higher operational temperatures
- Powerful polarity (or stickiness) to the tool surface protecting against wear and corrosion
- Strong anti-wear additives to protect the equipment
- Readily biodegradable for safer use in the environment
- Multiple ISO grades to keep you operational in a large temperature range
- Low odor
- Foam resistance
- Synthetic Blend for increased performance capability across a wider temperature range and in wet environments

SUITABLE USES

- Pneumatic “hammer” equipment such as rock drills, jackhammers, and pavement breakers
- Chipping hammers, demolition hammers and drifters used in mining
- Enclosed industrial gearboxes where leakage is a problem and oil must be continually added
- Pile drivers
- Riveters
- Oil and gas drilling
- Water well drilling
- Geotechnical drilling
- Geothermal drilling
- Mining Drills

COMPATABILITY

Equipment Compatibility

- Field tested and proven high performance in Atlas Copco, Halco, NUMA, and many others.

Lubricant Compatibility

- Compatible with most other types of lubricants for specific applications and lubricants please contact your BioBlend representative.

Seal & Paint Compatibility

- No known paint compatibility issues

APPLICATION / TECHNICAL SUPPORT

- Follow recommendations provided in your equipment owner’s manual
- Follow your organization’s best practices for preparation, cleaning, conversion, application, and ongoing maintenance practices
- **Technical Support** - If you have further questions, please fill out contact form on bioblend.com and one of our team will contact you to review your question(s)

APPROVALS / CERTIFICATIONS

- eSyn Certified
- Classified as environmentally acceptable lubricants (EAL’s) as per EPA standards for biodegradability, toxicity and bioaccumulation in aquatic environments.

PACKAGE SIZES

- 5 Gallon Pails
- 55 Gallon Drums
- 275 Gallon Totes

STORAGE

Keep in a cool, dry and well-ventilated place. Store in a properly labelled, original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. To help maintain product quality, do not store in heat or direct sunlight.

CAUTIONS

Ensure adequate ventilation. Do not breathe vapor/dust. Use personal protective equipment and avoid contact with skin, eyes, and clothing. Wash thoroughly after

handling. See the safety data sheet (SDS) for emergency, proper handling, and disposal information.

AVAILABILITY

Worldwide

TYPICAL PROPERTIES

Property	Test Method	SB RDP 100	SB RDP 150
Product Code		BLSBRDP100	BLSBRDP150
ISO Grade		100	150
Specific Gravity		.91	.91
Viscosity @ 40°C cS	D445	100	150
Viscosity @ 100°C cS	D445	18	25
Viscosity Index (VI)	D2270	>220	>220
Pour Point °F (°C)	D97	-30 (-34)	-25 (-32)
Flash Point °F (°C)	D92	>600 (315)	>600 (315)
Performance Properties			
Timken OK Load	D2509	>60lbs	>60lbs
Falex EP Fail Load	D3233	3500	3500
Copper Corrosion	D4048	1A	1A
Rust Test A&B	D665	PASS	PASS
Biodegradable % (meaning >60%)	OECD 301B	PASS	PASS
Tackifier		YES	YES

The values quoted above are typical of normal production. They do not constitute a specification.

BioBlend makes no representations, guarantees or warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose, or as to the correctness or sufficiency of data herein presented. All risk and liability regarding use, conditions of use and handling of this product are assumed by the buyer and any user. No agent, representative, or employee of this company is authorized to vary any of the terms of this notice. To continue to provide superior quality, BioBlend reserves the right to change the composition of its products without notice.

APPROVALS / CERTIFICATIONS LOGOS

